

FLAME RETARDANT WIRE

Lumicon - FLAME RETARDANT MULTI STRAND
single core unsheathed flexible cables in voltage grade upto and including 1100 V.



No. of Strands/ Nom. Dia. of Strand (mm)	Length in mtr.	Nom. area of cond. mm2
24 / 0.2	(90 mtr.)	0.75
14 / 0.3	(90 mtr.)	1.00
22 / 0.3	(90 mtr.)	1.50
36 / 0.3	(90 mtr.)	2.50
56 / 0.3	(90 mtr.)	4.00
84 / 0.3	(90 mtr.)	6.00
80 / 0.4	(90 mtr.)	10.0
126 / 0.4	(90 mtr.)	16.0
196 / 0.4	(90 mtr.)	25.0

No. of Strands/ Nom. Dia. of Strand (mm)	Length in mtr.	Nom. area of cond. mm2
24 / 0.2	(180 mtr.)	0.80
14 / 0.3	(180 mtr.)	1.00
22 / 0.3	(180 mtr.)	1.50
36 / 0.3	(180 mtr.)	2.50
56 / 0.3	(180 mtr.)	4.00
84 / 0.3	(180 mtr.)	6.00



SINGLE/TWIN CORE SOLID ALUMINIUM CABLE

Lumicon -SINGLE CORE PVC insulated Aluminum conductor sheathed weather proof
Service wire. (Black)

PVC insulated sheathed SINGLE CORE SOLID Aluminium cables upto & including 1100 Volts


No. of Strands/ Nom. Dia. of Strand (mm)	Length in mtr.	Nom. area of cond. mm2
1/1.78	(100 mtr.)	2.50
1/2.28	(100 mtr.)	4.00
1/2.80	(100 mtr.)	6.00
1/3.55	(100 mtr.)	10.0
1/4.51	(100 mtr.)	16.0
1/5.64	(100 mtr.)	25.0

PVC insulated sheathed TWIN CORE SOLID Aluminium cables upto & including 1100 Volts

No. of Strands/ Nom. Dia. of Strand (mm)	Length in mtr.	Nom. area of cond. mm2
1/1.78	(100 mtr.)	2.05
1/2.28	(100 mtr.)	4.00
1/2.80	(100 mtr.)	6.00
1/3.55	(100 mtr.)	10.0
1/4.51	(100 mtr.)	16.0
1/5.64	(100 mtr.)	25.0

No. of Strands/ Nom. Dia. of Strand (mm)	Length in mtr.	Nom. area of cond. mm2
1/1.78	(450 mtr.)	2.50
1/2.28	(450 mtr.)	4.00
1/2.80	(450 mtr.)	6.00
1/3.55	(450 mtr.)	10.0
1/4.51	(450 mtr.)	16.0
1/5.64	(450 mtr.)	25.0

MULTICORE ROUND CABLE



Lumicon - FLAME RETARDANT MULTI STRAND

single core unsheathed flexible cables in voltage grade upto and including 1100 V.

No. of Strands/ Nom. Dia. of Strand (mm)	Length in mtr.	Nom. area of cond. mm ²	Cable Type
16/0.2	100 Mtr	0.50	2 Core
24/0.2	100 Mtr	0.75	2 Core
14/0.3	100 Mtr	1.00	2 Core
22/0.3	100 Mtr	1.50	2 Core
36/0.3	100 Mtr	2.50	2 Core
56/0.3	100 Mtr	4.00	2 Core
84/0.3	100 Mtr	6.00	2 Core
80/0.4	100 Mtr	10.0	2 Core
16/0.2	100 Mtr	0.50	3 Core
24/0.2	100 Mtr	0.75	3 Core
14/0.3	100 Mtr	1.00	3 Core
22/0.3	100 Mtr	1.50	3 Core
36/0.3	100 Mtr	2.50	3 Core
56/0.3	100 Mtr	4.00	3 Core
84/0.3	100 Mtr	6.00	3 Core
80/0.4	100 Mtr	10.0	3 Core
16/0.2	100 Mtr	0.50	4 Core
24/0.2	100 Mtr	0.75	4 Core
14/0.3	100 Mtr	1.00	4 Core
22/0.3	100 Mtr	1.50	4 Core
36/0.3	100 Mtr	2.50	4 Core
56/0.3	100 Mtr	4.00	4 Core
84/0.3	100 Mtr	6.00	4 Core
80/0.4	100 Mtr	10.0	4 Core

SOLAR CABLES



No. of Strands/ Nom. Dia. of Strand (mm)	Length in mtr.	Nom. area of cond. mm ²	Price
56 / 0.3	500 Mtr	4	11350
84 / 0.3	500 Mtr	6	17150
140 / 0.3	500 Mtr	10	26400

INTRODUCING

